


Built-in Mech-Sensor

Precision technology creates a lineup of versatile Label Applicators that meet a wide range of label and sticker needs!








A Mech-Sensor combines with a sensor that automatically detects labels of different strokes to eliminate the need for manual alignment when you load labels.

- For pre-printed general roll labels.
 No special (punched or slit) labels or separators required.
- Supports use of label size from 18 x 20mm up to 60 x 100mm.






 MODEL
 LABEL GAP(mm)
 LABEL SIZE(mm)
 MAX. OUTSIDE DIAMETER(mm)


 APN-30
 2-3
 18-60
 25-60
 100

 APN-100
 50-100
 100
 100

The Mech-Sensor catches the label and

catches the label and automatically detects the stroke for smooth feeding.









A new slidable Mech-Sensor provides support for round, oval, and other non-rectangular shape labels.

- For eye-catching labels of various shapes that appeal to customers.
- Supports use of the label size from 20 x 20mm up to 60 x 100mm.
 For pre-printed general roll labels.
 No special (punched or slit) labels or separators required.



▲ Slidable Mech-Sensor



Slide The Mech-Sensor to the left or right until it is in the center of the label.

M	MODEL	LABEL GAP(mm)	LABEL SIZE(mm)		MAX. OUTSIDE
	MODEL		STROKE	WIDTH	DIAMETER(mm)
	APF-30	2-3	20-60	20-30	100
	APF-60			20-60	
	APF-100			20-100	





The smaller the label it is when you dispense, the more troublesome it becomes..... It assures high performance for small labels.

The new type of a premium tool, APN10-30 assures high performance for samll labels.

- For pre-printed general roll labels.
 No special (punched or slit) labels or separators required.
- Supports use of label size from 10x30mm up to 60x30mm.

	MODEL	LABEL GAP(mm)	LABEL SIZE(mm)		MAX. OUTSIDE
			STROKE	WIDTH	DIAMETER(mm)
	APN10-30	2-3	10-60	20-30	100

Notice

- Labels must be more than 50 µm thick for all models.
- Some types of film, synthetic paper, and other special labels may not be supported.
- Please ask our distributor for details before using special labels.
- We reserve the right to change specifications without notice for improvement.

OJP PAT. 2708677, 2708680

TOWA CO.,LTD.

Ginza YK Bldg., #10-9, Ginza 5-chome, Chuo-ku, Tokyo 104-0061, Japan Tel:+81-3-3572-9621 Fax:+81-3-3572-9620 http://www.towa.jp/export/ e-mail: export@towa-ltd.co.jp

