



Epson TM-T88VI

Reliable, ultra-fast reciept printer with state of the art mobile connectivity

Connect to multiple devices simultaneously

Ultrafast print speed of up to 350 mm/s

Reliability you can count on

Easy printing from mobile devices

Print from web-based applications

Triple interface connectivity to future proof growing businesses

Epson TM-T88VI

| Product Specifications | | | |
|-------------------------|---|----------------------|--|
| PAPER | | COLOUR | Black / White |
| PAPER SIZE | 80mm: 79.50 ± 0.50 (W) mm x dia 83.00 mm | INSTALLATION | Horizontally, wall hanging |
| | 58mm: 57.50 ± 0.50 (W) mm x dia 83.00 mm | INTERFACE CONNECTORS | D.K.D. function |
| FONTS & STYLES | | HUMIDITY | Operation 10% - 90% |
| PRINT SPEED | 350 mm/s | TEMPERATURE | Operation 5° C - 45° C, Storage -10° C - 50° C |
| PRINT SPEED (DEFAULT) | 300 mm/s | STANDARD COMPLIANCE | , , |
| PRINTING FONT | Font A (default): 12 x 24 | SAFETY APPROVALS | RCM: AS / NZS CISPR class A |
| | Font B: 9 x 17 (including 2-dot horizontal spacing) | | Energy-saving: ENERGY STAR |
| COLUMN CAPACITY RECIEPT | 80mm: 42/48/56 columns | OTHER | 3, |
| | 58mm: 30/36/40 columns | WARRANTY | 48 months |
| CHARACTER SIZE | Font A: 1.41 x 3.39 (W x H mm) | WHAT'S IN THE BOX | |
| | Font B: 0.99 x 2.40 (W x H mm) | | Connector cover |
| CHARACTER SET | 95 Alphanumeric, 18 set International, 128 x 43 Graphic | | Main unit |
| PRINTING CHARACTERS | Text (incl. Euro symbol), Graphics, Barcode | | PS-180 & AC cable |
| INTERFACES | | | Paper spacer |
| CONNECTIVITY | Built-in USB, Built-in Ethernet (10/100Base-T/TX) + | | Power switch cover |
| | UIB (Serial, Parallel, Powered USB) | | Roll paper |
| | Bluetooth 2.1+EDR (dedicated model) | | Setup guide |
| | Wireless (USB wireless dongle): OT-WL05 (802.11 | | Warranty document |
| | a/b/g/n) or OT-WL02 (802.11 b/g/n) | OPTIONAL ACCESSORIES | |
| | Beacon (using Bluetooth low energy): Beacon dongle | C32C845040 | WH-10 (040) Wall hanging bracket |
| | (Epson approved dongle: Laird model BT-820) | C32C890739 | OT-WL02 (739): Wireless LAN Dongle, 2.4 GHz |
| DATA BUFFER | | C32C814596 | Power supply cover |
| DATA BUFFER | 45 Bytes or 4 kb, selectable | CONFIG BUILDS | |
| POWER | 80 400 40 44 | C31CE94241 | TM-T88VI-241 Built-in ethernet, USB, serial, |
| POWER SUPPLY | PS-180, AC cable | | dark grey |
| OPERATING VOLTAGE | 24 V | C31CE94243 | TM-T88VI-243 Built-in ethernet, USB, parallel, |
| POWER CONSUMPTION | Operating: 27.6W | | gark grey |
| OFMEDAL | Stand by: 0.5W | C31CE94581 | TM-T88VI-581 Built-in ethernet, USB, BT:0S |
| GENERAL | 445 405 440 AMERI D. II. II.' III | | dark grey |
| PRODUCT DIMENSIONS | 145 x 195 x 148 mm (Width x Depth x Height) | COVER PLUS (OPTION) | 0 0 0 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 |
| PRODUCT WEIGHT | 1.6 kg | 1YWT88VI | CoverPlus 1yr service pack TM-T88VI |

For more information visit us on www.barcodes.com.au/Epson-TM-T88VI-Printer or call us on 1300 800 999.



Phone: 1300 800 999

Email: sales@barcodes.com.au Website: www.barcodes.com.au

Better Products for a Better Future













Epson is the registered trademark of Seiko Epson Corporation. All other names and company names used herein are for identification purpose only and may be the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. All print samples shown herein are simulations. Specifications are subject to change without notice.

EPSON AUSTRALIA

3 Talavera Road North Ryde NSW 2113 Tel: (02) 8899 3666 www.epson.com.au ABN 91 002 625 783

EPSON NEW ZEALAND

Level 2 7-9 Fanshawe Street Auckland, 1010 Tel: 0800 443 478 www.epson.co.nz 06/17



