





Epson ColorWorks CW-C6510

Highly dependable 8" commercial inkjet label printer covering the full spectrum of label sizes for enhanced productivity and versatility.

- Reliable Engineered by Epson for demanding applications
- Enhanced productivity Eliminates the need to pre-print
- Astounding image quality up to 1200 dpi resolution with spot colour
- matching function
- Seamless integration Compatible with ZPL II, major middleware and OS
- Versatile application Peel-and-present and auto-cutter options available

Epson CW-C6510



Designed for businesses transiting from thermal transfer label printers

The CW-C6510 provides an easy transition for customers looking to upgrade their thermal transfer printers to colour inkjet label printer. It features similar media handling capabilities, speed, features and connectivity options that deliver seamless integration with existing workflow.

Versatile and easy to use

The CW-C6510 features a large 2.7" colour LCD status panel with multi-language support for ease of use. It also caters to a wide range of applications with its auto-cutter/peeler modules that supports print-on-demand and Peeland-Present applications.

Quality and reliability you can count on

The CW-C6510 is the ideal choice for businesses that requires fast print speed with enhanced reliability. Based on Epson's PrecisionCore printing technology, the CW-C6510 delivers the quality and reliability that Epson is known for, which ensures an easy, reliable printing solution.

Product Specifications

Printing method	Serial inkjet (PrecisionCore TFP)		
Printing speed	85 mm/s (max)		
Printing resolution	1200 dpi x 1200 dpi (max)		
Printing width Max. 211.9 mm			
Colours	4 colours		
Format	Roll media, fanfold media		
Туре	Matte paper label, synthetic label, glossy paper label, glossy film label, high glossy paper label		
Roll media shape	Continuous label (BM or w/o BM), Die-cut label (Gap or BM)		
Fanfold media shape	Die-cut label (BM)		
Roll Diameter	Max. 152.4 mm		
Media width (back paper width)	25.4 mm – 215.9 mm		
Carriage life	6 mil. pass		
Paper feeding mechanism life	ife 200 km or 1.5 mil. pages		
Auto-cutter life (for A/C model) Die-cut label backing: 1.5mil. cuts, continuous label (matte): 0.2mil. cuts, continuous label (synthetic):0.1mil cuts, continuous label			
Power	100 ~ 240V AC		
Operating	230V: average approximately 38.7 W		
Stand-by	230V: average approximately 5.82 W		
Power off state	230V: average approximately 0.24 W		
Interface	USB2.0, Ethernet 1000Base-T / 100Base-TX / 10Base-T		
Extended interface Dsub-25 pin			
Product dimensions	444 x 515 x 326 mm (width x depth x height)		
Weight*	Peeler model: Appx.26.3 kg, A/C model Appx.25.5 kg *Not including the ink cartridge and roll media.		
Commands	ESC/Label		
Operating systems	Windows 10, 8.1, 8, 7 SP1, Vista SP2, XP SP3 or later, Server 2019, 2016, 2012 R2, 2012, 2008 R2, 2008, 2003 R2 (32-bit), Mac OS X 10.6.8, Mac OS X 10.7.x, Mac OS X 10.8.x, Mac OS X 10.9.x, Mac OS X 10.10.x, Mac OS X 10.11.x, Mac OS X 10.12.x, Mac OS X 10.13.x, Mac OS X 10.14.x		
	One year		
	Printing speed Printing resolution Printing width Colours Format Type Roll media shape Fanfold media shape Roll Diameter Media width (back paper width) Carriage life Paper feeding mechanism life Auto-cutter life (for A/C model) Power Operating Stand-by Power off state Interface Extended interface Product dimensions Weight* Commands		

Ordering information

Printer		Consumables	
ColorWorks C6510A (Autocutter)	CW-C6510A-108	SJMB6500	C33S021501
ColorWorks C6510P (Peeler)	CW-C6510P-208	SJIC36P-K	C13T44C140
		SJIC36P-C	C13T44C240
Options		SJIC36P-M	C13T44C340
Paper Holder C6500	C32C881101	SJIC36P-Y	C13T44C440





Phone: 1300 800 999

Email: sales@barcodes.com.au Website: www.barcodes.com.au