

PM550

RUGGED ANDROID HANDHELD POWERED FOR THE WAREHOUSE

Align your enterprise mobility platforms with Android

Android has become the operating system of choice for rugged handheld terminals even in the warehouse. Leading this shift is PM550 with Android Nougat 7.1, including enterprise-tuned features such as the Enterprise Mobility Kit(EmKit) - a world proven, customized kit designed precisely for the enterprise mobility market. Receive quality system support that makes out of the box deployment extremely fast and painless, only for Android models.

A new 4.3-inch display, all with more power

Run whatever tasks you need on the new 4.3-inch touch screen with maximized visibility, which feels even bigger with no virtual keypad popping up to disturb your view. Keeping the large display on is a primary removable battery of 6,300mAh that allow your workers the full capability to get the work done. We expanded the screen and gave it more power than any competing device – the combination to enhance the productivity of your workforce.

Unshakable reliability even in the harshest conditions

We know how tough your workplaces can get for your handheld devices, and not all survive. PM550 is a heavy-duty mobile terminal with a MIL-STD -810G for 1.5 meter(5.0ft) drop resistance and has an IP65 rating, which means it is impenetrable to water and dust, can survive numerous drops as well as shock, vibration, dramatic temperatures, and more extreme conditions. Moreover, the double-molded bumper on every edge of the device along with a Gorilla Glass 3 touch screen is an added plus, making PM550 the handheld you can count on.



Keep the momentum going with the fastest wireless connections

When you are out in the warehouse, the quality of your device's wireless connection should be the least of your worries. PM550 is one of the very few Android devices in the world that supports 802.11r with the fastest fast-secure roaming method, Cisco CCKM, to ensure seamless roaming regardless of signal channel, strength, or load. Let PM550 clear your path for business – no delay, at no cost.

Scanning performance that focuses on what's important

The standard range 1D/2D imager reads all GS1 symbologies as well as poorly printed barcodes, and extra long imager range option is also available for scanning barcodes as far as 11 meters. As a new scanning solution, the PM550 supports Extended Wedge, a feature which enables selective modification of a decoded value. There is no need for extra costs for SW development, or the excess time set aside for the sorting and collecting of data. Save your resources immensely by merely adjusting your scanning settings to capture just the data you need.



PM550

PHYSICAL CHARACTERISTICS Dimensions With standard batt. 204.5mm L x 79mm W x 175mm D 8.05 in. Lx 3.11 in. Wx 6.88 in D 586g / 20.67oz Weight 4.3", IPSpanel (480 x 800 pixel) WVGA Display Exceptionally bright Daylight readable (500 nits typical) **Touch Panel** Multi-touch capacitive Corning Gorilla glass Power Main Battery 3.63V, 6,300mAh removable Back-up Battery 3.7V, 60mAh (Hot-Swap) Keypad 2 Keypadoptions 24 KeyNumeric (Shifted alpha), (backlit keys) 51 Key Alpha Numeric Standard High speed USB 2.0 type-Cport Communications Notification Top-front, bottom, touch panel dual color LEDsfor scanning and charging Vibrator Beeper PERFORMANCE CHARACTERISTICS Main-Processor Qualcomm® APQ80161.2GHz Quad Core 64-bit CPU Operating System

Gooale Android 7.1.2 Nougat (CTS& GMScertified)

Memory and Storage

mennory	and otorage	
RAM	2GB	
ROM	16GB	

Sensor

Accelerometer sensor

USERENVIRONMENT

Operating Temperature	-20°Cto 60°C/ -4°Fto 140°F
Storage Temperature	-25°Cto 70°C/ -13°Fto 158°F
Humidity	95% Non-condensing
Drop	Multiple 5'/ 1.5m drops to concrete ove the operating temperature
	Multiple 6' / 1.8m drops to concrete at ambient temperature 73°F/23°C; meets and exceeds MIL-STD-810G
Rain / Dust Proof (Sealing)	IP65

500 cycles (1,000hits) at 1m / 3.3 ft

Tumble

POINT

🕥 Barcodes.com.au

Nobile

Phone: 1300 800 999 Email: sales@barcodes.com.au Website: www.barcodes.com.au

±15 kV air discharge Electrostatic Discharge ±8 kV contact discharge DATA CAPTURE Ir 2 S ra 2 ra *F Е W

Wireless LAN	
Radio	IEEE802.11a/b/g/n/d/h/i/k/r/v, IPv4, IPv6, 1X1 SISO
Data Rates	IEEE802.11a/n: Up to 150 Mbps IEEE802.11b/g/n: Up to 72.2 Mbps
Operating Channels	1 to 13 (2412~2472MHz), 36 to 165 (5180~5825MHz)
Channel Bandwidth	20, 40 MHz
Security and Encryption	WEP(40or 104bit) WPAWPA2 Personal(TKIP, AES); WPAWPA2 Enterprise(TKIP/AES) - PEAP(MSCHAPv2, GTC), TLS, TTLS(PAP, MSCHAP, MSCHAPv2, GTC), PWD, SIM, AKA, AKA', LEAP, Supports FAST(MSCHAPv2,GTC)
Fast Roam	PMKID Caching, Cisco CCKM,802.11r
Wireless PAN	
Bluetooth	Integrated Bluetooth Class Ver 4.1

0 to 78 (2402-2480MHz) Channels 1, 2, 3Mbps

REGULATORY APPROVALS AND COMPLIANCE

CB, CE, FCC, IC, TELEC, IFETEL, CCC, SRRC, RCM, WPC, BIS, CU, FAC. TRC. TRA. CITC. KC. RoHS

ENTERPRISE SOLUTION

SOTI, Airwatch, Teamviewer



Power Launcher

Direct Clone

ntegrated Barco 2D Mid-range ccanner	de Reader Readsup to 81.9 cm (20 mil C39)			
D Extra-long ange Imager	Readsup to 13 meters (100 mil Code 128)			
2D Extra-long ange Imager	Readsup to 11 meters (100 mil Data Matrix)			
Follows the specifications of the scanner manufacturer.				
Extended Wedge	Edit your decode value			
VIRELESS				
Vireless LAN Radio	IEEE802.11a/b/g/n/d/h/i/k/r/v, IPv4, IPv6.1X1 SISO			

1 to 13 (2412~2472MHz), 36 to 165 (5180~5825MHz) 20, 40 MHz WEP(40or 104bit) WPA/WPA2 Personal(TKIP, AES); WPA/WPA2 Enterprise(TKIP/AES) - PEAP(MSCHAP/2, GTC), TLS, TTLS(PAP, MSCHAP/3, GTC), PWS, Supports FAST(MSCHAP/2,GTC) PMKID Caching, Cisco CCKM,802.11r	1222002.11b/g/11. 0p to 72.2 Mbp3	
WEP(40or 104bit) WPAWPA2 Personal(TKIP, AES); WPAWPA2 Enterprise(TKIP/AES) - PEAP(MSCHAPv2, GTC), TLS, TTLS(PAP, MSCHAP, MSCHAPv2, GTC), PWD, SIM, AKA, AKA', LEAP, Supports FAST(MSCHAPv2,GTC)		:
WPAWPA2 Personal(TKIP, AES); WPAWPA2 Enterprise(TKIP/AES) - PEAP(MSCHAPv2, GTC), TLS, TTLS(PAP, MSCHAP, MSCHAPv2, GTC), PWD, SIM, AKA, AKA, LEAP, Supports FAST(MSCHAPv2,GTC)	20, 40 MHz	
	WPA/WPA2 Personal(TKIP, AES); WPA/WPA2 Enterprise(TKIP/AES) - PEAP(MSCHAP/2, GTC), TLS, TTLS(PAP, MSCHAP, MSCHAP/2, GTC), PV/D, SIM, AKA, AKA', LEAP, Supports FAST(MSCHAP/2,GTC)	1

Integrated Bluetooth ClassI, Ver. 4.1 Bluetooth

Data Rates



Kiosk mode with system restriction Allows admin to restrict operator's access to system settings, MTP connection and screen capture Master PDA becomes a local server for a nearby Point Mobile device to



automatically communicate and download/restore backup files Unique two-step feature for Point Mobile Android models that enables the fastest device deployment right out of the box

WARRANTY

Subject to the Terms and Conditions, PM550 carries 1 (one) year-warranty period from the date of purchase against the defective materials and manufacturing defects. Point Special and Premium Care service is recommended.

For the further inquiry, please contact: service@pointmobile.co.kr

ACCESSORIES



For more information visit https://www.barcodes.com.au/point-mobile-pm550-mobile-computer/ or call us on 1300 800 999

Google, Android, Google Play and other marks are trademarks of Google LLC. Copyright © 2006-2019 Point Mobile Co.,Ltd. All rights reserved. Point Mobile Co.,Ltd. is the designer and manufacturer of handheld mobiles. Point Mobile Co.,Ltd. Logo are registered trademarks and symbols of Point Mobile Co.,Ltd. Features and specifications are subject to change without prior notice.