



## HT200e - “Smart & Easy” Stand-Alone Printer

- Direct Thermal
- Stand-Alone or Online
- Automatic Calculations
- Optional Battery Pack
- Easy Supply Loading
- Simple To Maintain
- Easy To Program

SATO's new HT200e printer is a new stand-alone printer which has been specially developed to fill the gap between basic hand labelers and large desktop labeling systems. This unique stand-alone machine is extremely user-friendly and prints labels and barcodes at the touch of a button.

It's fast, versatile, easy to use, and provides low cost solutions to a variety of labeling problems in both the retail and industrial sectors.

### Designed for the following applications:

- General Retail Labeling
- Medical/Pharmaceutical
- Bakeries/Deli
- Cosmetics
- Sales Tax Calculations
- Item Identification
- Price Marking
- Jewelry
- Fast Food
- Stock Control
- Sequential Numbering
- Mark Down Labels

# SATO HT200e Printers



## HT200e

<b>Printing Method</b>	Direct Thermal
<b>Print Resolution</b>	203 dpi (8 dots/mm)
<b>Print Speed</b>	Up to 2 ips (60 mm/sec) Battery Operated Up to 3 ips (80 mm/sec) AC Adapter
<b>Max. Print Width</b>	1.89" (48 mm)
<b>Max. Print Length</b>	3.78" (96 mm)
<b>Media Size</b>	Min. 1.1" (28 mm) W x 0.63" (16 mm) L Max. 2" (51 mm) W x 4" (103 mm) L
<b>Dimensions</b>	5.2" W x 9.06" D x 5.94" H (132 mm W x 230 mm D x 151 mm H)
<b>Weight</b>	5.3 lb (2.4 kg) without Battery Pack 5.5 lb (2.5 kg) with Battery Pack

### Features:

- Auto Power off (5 min)
- Calendar (Standard)
- Back lit LCD  
(16 Characters x 3 Lines)
- 2 Color Direct Thermal Printing

### Memory:

512K Bytes SRAM  
2 MB SRAM Card (optional)

### Processor:

32-Bit RISC

### Media:

Caliper: 5.5 - 7.48 MIL  
Core Diameter: 1" (25.5 mm)  
Max. Roll O.D.: 2.95" (75 mm)

### Sensing:

Reflective Sensor for I-Marks

### Interface Connection:

RS232C Serial Interface  
Scanner (RS232C)

### Barcode Symbolologies:

UPC-A/-E, EAN-8/13, Code39, Code128,  
I2/5, NW-7

### Barcode:

2:1, 2.5:1, 3:1 ratio;  
barcode height 1 to 240 dots

### Human Readable Fonts:

8 fonts including 4 useful POP characters

### Rotation:

Font: 0°, 90°, 180°, 270°  
Barcode: 0°, 180°

### Self Check Function:

Paper End; Cover Open; Test Print; Battery  
Level Check; Head Check

### AC Power:

100V/230V; Voltage + 8.4 V  
(Manual Select)  
Consumption: Max. 71VA 43W

### Options:

Battery Pack & Charger, SRAM Card (2MB),  
Touch or Pen Scanner



**SATO**  
DCS & Labeling Worldwide

 **Barcodes.com.au**

Phone: 1300 800 999  
Email: sales@barcodes.com.au  
Website: www.barcodes.com.au