

# RS6100 Bluetooth Wearable Scanner

## Maximum versatility, power and performance

Introducing Zebra's most powerful and versatile wearable scanner — the RS6100. This small and practically weightless wearable scanner is less than half the size and weight of its predecessor, the RS6000. An advanced multi-focus scan engine captures 1D and 2D barcodes at close range and on the top shelf of a rack 40 ft./12.2 m away, regardless of condition — scratched, dirty, poorly printed, under shrinkwrap and more. With five interchangeable wearing options, there's a style that will maximize comfort for every user. Use it anywhere — from warehouse aisles, freezers and coolers to the seat of a fork truck and out on the dock in rain, snow, blazing summer heat or subzero winter cold. The RS6100 is always in service with its removable battery — no downtime needed for charging, just swap in a fully charged battery. Choose cordless freedom with two battery options or corded battery-free operation. And since the RS6100 and RS5100 share common trigger assemblies, batteries and mounts, upgrading from the RS5100 is easy and cost-effective.



### Maximum versatility

#### Small and practically weightless

The RS6100 is less than half the size and weight of its predecessor, the RS6000 — just over two ounces and two cubic inches.

#### Cordless or corded — it's your choice

Pair with any Bluetooth-enabled Zebra enterprise-class handheld, tablet, wearable or vehicle mount mobile computer to utilize the full feature set of the RS6100— or pair with any existing Bluetooth smartphone, tablet or PC. Want to eliminate the need for batteries with corded operation? Power the RS6100 via a corded adapter that

connects to select Zebra mobile devices, including wearable and handheld computers.

#### Five interchangeable wearing styles

Five different mounts provide users with the freedom to choose the wearing style they prefer to maximize comfort, simplify task execution — and increase job satisfaction. All mounting accessories are interchangeable — swap at any time to maximize user comfort for scan-intensive tasks. The Enterprise Hand Mount accessory gives every hand a snug, comfortable and secure custom fit with a range of sizes for right and left hands — and users can adjust the scanner position on the hand to achieve the perfect balance and optimal scan angle for the ultimate in comfort and user productivity. For workers who prefer to wear the scanner on one finger, there are two single finger mount options — single and double triggers. The single trigger can be removed and rotated, allowing users to easily switch between left and right finger mounting. The double trigger enables workers to change hands on the fly — without removing the trigger. All triggers support continuous scanning mode. And the optional vibrating trigger signals an error or exception, allowing users to take corrective actions. The ambidextrous, one-size-fits-all back of hand mount accommodates gloves and easily fits into the smallest of spaces. And a retracting lanyard trigger worn around the neck or on a belt keeps the scanner handy, yet out of the way.

#### Use it everywhere — including the freezer

Use the RS6100 in freezers and coolers, out on the dock in the sweltering heat and subzero cold, rain, snow — the RS6100 is built to handle it all.

**Instant pairing — just tap and go**

With NFC, simply tap the RS6100 on NFC-enabled Zebra devices — no need to scan a pairing barcode or open Bluetooth settings to identify and select the device.

**Direct users with programmable line-of-sight LEDs**

Programmable multiple LEDs on the back of the RS6100 can provide users with feedback to improve productivity and task accuracy — confirm successful scans, direct users through the fastest path to the right item and more.

**Prevent the spread of germs with personal trigger assemblies**

A modular two-piece design separates the trigger assembly from the scanner body. Since only the trigger assembly touches skin, you can give each worker their own trigger.

**Maximum power and performance****Unmatched advanced range scanning**

The SE55 1D/2D Advanced Range scan engine with Intellifocus™ technology provides an extraordinary scanning range that is more than double the range of the RS6000 — enabling just about any use case. Easily capture barcodes on items in hand and on the top shelf of a rack — from 2 in./5.08 cm to 40 ft./12.2 m. Zebra's exclusive PRZM Intelligent Imaging software ensures fast and accurate capture of barcodes in virtually any condition — scratched, dirty, poorly printed, damaged, under shrinkwrap and low contrast. And with the highest resolution sensor in its class, the RS6100 can capture even the smallest, densest barcodes.

**An advanced removable and replaceable battery**

With removable and rechargeable batteries, you never need to take the RS6100 out of service for charging, maximizing value and your return on investment. Choose from two PowerPrecision+ batteries — standard or extended. The standard battery lasts a full shift, while the extended battery powers longer shifts. And with PowerPrecision Console, a no-cost Mobility DNA tool that runs on the host Zebra mobile device, you can easily spot and discard aging batteries that can no longer hold a full charge to power a full shift, protecting productivity.

**Maximum durability, reliability and management simplicity****Rugged and ready for constant use**

The RS6100 is triple tested for durability — sealing, drop and tumble.

Drop it on concrete and hose it off — no problem. Only the RS6100 is drop tested across the entire temperature range — no need to worry about brittle plastics shattering in the cold or expansion of parts on a hot summer day, delivering unmatched reliability.

**No Wi-Fi interference — guaranteed**

Wi-Fi Friendly Mode eliminates potential interference between Bluetooth on the RS6100 and Wi-Fi on other mobile devices.

**Triggers built for intensive scanning**

The triggers are rated for millions of actuations — instead of the typical few hundred thousand trigger presses. The result — less frequent replacement of triggers and a lower total cost of ownership (TCO).

**Minimize downtime with maximum replaceable parts**

The removable and swappable battery and trigger assemblies minimize trips to the service depot and maximize lifecycle. The charge contacts and vibration engine are also integrated into the trigger assembly, enabling replacement of these components right on site, cost-effectively — with virtually no downtime.

**Save time and money with high capacity chargers**

High capacity ShareCradles can charge 20 RS6100 ring scanners or 40 RS6100 batteries, reducing backroom cost and management time. For example, use just five high-capacity RS6100 ShareCradles to charge 100 scanners — instead of 100 USB charging cables.

**Maximum upgrade simplicity****Easily and cost-effectively upgrade from the RS5100**

If you are currently using Zebra's RS5100 Wearable Scanners and want to upgrade to the most flexible scanning range, it's easy — many accessories and mounts work with the RS6100. Use your existing RS5100 single and double trigger assemblies on your new RS6100 scanners. Your existing RS5100 batteries are also compatible with the RS6100 — including standard and extended batteries, plus the RS5100 8-slot and 40-slot battery chargers. And the new updated Enterprise Hand Mount, Back of Hand Mount and Lanyard Mounts are compatible with both the RS5100 and the RS6100, simplifying accessory management in mixed deployments.

# Specifications

Physical Characteristics	
<b>Dimensions</b>	2.62 in. L x 1.29 in. W x 0.83 in. D (2.8 cubic inches) 66.6 mm L x 32.7 mm W x 21 mm D
<b>Weight</b>	With 1x battery: 2.47 oz./70 g With 1.5x battery: 2.68 oz./76 g
<b>Optical Resolution</b>	2688 x 1520 pixels
<b>Roll</b>	360°
<b>Pitch</b>	±60°
<b>Skew</b>	±60°
<b>Aiming Element</b>	515 nm Laser
<b>Illumination Element</b>	1 warm white LED
<b>Field of View</b>	Horizontal: 37°, Vertical: 21.4°
<b>Ambient Light Immunity (from total darkness)</b>	Max 107,639 lux (direct sunlight)
<b>Supported 1D Symbologies</b>	Code 39, Code 128, Code 93, Codebar/NW7, Code 11, MSI, UPC/EAN, I 2 of 5, Korean 3 of 5, GSI DataBar, Base 32 (Italian Pharma)
<b>Supported 2D Symbologies</b>	PDF417, Micro PDF417, Composite Codes, TLC-39, Aztec, DataMatrix, MaxiCode, QR Code, Micro QR, Chinese Sensible (Han Xin), Postal Codes
<b>Supported OCR Symbologies</b>	OCR-A, OCR-B
<b>Power</b>	480 mAh standard; 735 mAh extended; PowerPrecision+; Li-ion battery pack; corded adapters for WT6000, WT6300, TC21/26 and TC53/58
<b>Network Connections</b>	WPAN (Bluetooth)
<b>Scanner</b>	SE55 1D/2D Advanced Range Scan Engine with IntelliFocus™ technology
<b>Pairing</b>	NFC; Tap to Pair
Performance Characteristics	
<b>User Environment</b>	RoHS Directive 2011/65/EU; Amendment 2015/863 REACH SVHC 1907/2007
<b>Operating Temperature</b>	32° F to 122° F/0° C to 50° C with standard battery -22° F to 122° F/-30° C to 50° C with extended battery
<b>Storage Temperature</b>	-40° F to 140° F/-40° C to 60° C including battery -40° F to 158° F/-40° C to 70° C excluding battery
<b>Humidity</b>	5% - 95% non condensing
<b>Drop Specification</b>	Multiple 6 ft./1.8 m drops to concrete over the operating temperature range
<b>Tumble Specification</b>	1,000 1.64 ft./0.5 m tumbles
<b>Sealing</b>	IEC 60529: IP65
<b>Vibration</b>	Sine 5-2000Hz, 4g peak, 1 hour per axis; Random 20-2000Hz, 6g RMS or 0.04g2/Hz, 1 hour per axis
<b>Electrostatic Discharge (ESD)</b>	±15kVdc air discharge; ±8kVdc contact discharge
User Interface	
<b>LED</b>	4 RGB LEDs located at the back side of the device (programmable)

<b>Beeper</b>	Up to 85 dBA @ 10 cm from the back of the device beeper port
<b>Restore Key</b>	User accessible for emergency warm boot and Bluetooth reconnect (after disconnect timeout)
<b>Scan Triggering</b>	Manual ambidextrous trigger
<b>Bluetooth</b>	Class 1 and 2, Bluetooth v5.0 with Bluetooth Low Energy (BLE) Supporting profiles: Serial Port Profile (SPP), Human Interface Device Profile (HID), Service Discovery Application Profile (SDAP)

### Warranty

Subject to the terms of Zebra's hardware warranty statement, the RS6100 is warranted against defects in workmanship and materials for a period of 1 (one) year from the date of shipment. For complete warranty statement, go to [www.zebra.com/warranty](http://www.zebra.com/warranty)

### Recommended Services

Zebra OneCare Essential and Select: Maximize Zebra device availability, device value and operational efficiency with these fully-featured support services that set the industry bar for support.

## Markets and Applications

### Warehousing/ Distribution

- Warehouse management
- Receiving
- Picking
- Put away
- Sorting
- Loading

### Manufacturing

- Inventory management
- Replenishment
- Parts tracking
- Sortation
- Assembly
- Finished goods verification

### Transportation and Logistics

- Warehouse management

### Retail

- Back of store warehouse management
- Receiving
- Inventory management
- Sortation

**PRODUCT SPEC SHEET**

RS6100 BLUETOOTH WEARABLE SCANNER



1300 800 999

sales@barcodes.com.au

<https://www.barcodes.com.au/>

Unit 13, 51 Moreland Rd, Coburg, Victoria, 3058, Australia



---

ZEBRA and the stylized Zebra head are trademarks of Zebra Technologies Corp., registered in many jurisdictions worldwide. All other trademarks are the property of their respective owners. ©2022 Zebra Technologies Corp. and/or its affiliates. 11/14/2022.